

Production of granulated binder for hydraulic building material

Bibliographic data	Description	Claims	Mosaics	Original document	INPADOC LEGAL status
Patent number:	DE19610561				
Publication date:	1997-09-25				
Inventor:	MOEDINGER HILDEGARD (DE)				
Applicant:	MOEDINGER HILDEGARD (DE)				
Classification:					
- international:	C04B7/52; C04B18/02; C04B40/06; C04B7/00; C04B18/00; C04B40/00; (IPC1-7); C04B40/00; C04B22/06; C04B22/14; C04B24/04; C04B24/14; C04B24/18; C04B24/26; C04B24/38; C04B28/00				
- european:	C04B7/52A2; C04B18/02L; C04B40/06A				
Application number:	DE19961010561 19960318				
Priority number(s):	DE19961010561 19960318				
View INPADOC patent family					
Report a data error here					
<p>Abstract of DE19610561</p> <p>Process is for the production of granulated binders for building materials, which undergo setting by hydration. The process comprises (a) converting a surfactant-containing aqueous starting mixture into a rigid, water-containing foam which also contains adhesive additives and/or setting retarders, (b) mixing this with a powdered binder (I) to form a pre-granulate consisting of binder powder adhering to a moist foam core, and (c) drying at above 100 deg C before the onset of any appreciable hydration of the binder by moisture from the foam core. Also claimed is a granulated binder obtained by this process.</p> <p style="text-align: center;">Data supplied from the esp@cenet database - Worldwide</p>					